

1. Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product Identity	SAF-T-EZE NICKEL PREMIUM ANTI-SEIZE
Alternate Names	Part Numbers: 80612, 80622, 80627, 80637, 80653, 80657, 80660, 80665, 80678, 80689, 80699 Product Type: Lubricating Grease

1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use	See Technical Data Sheet.
Application Method	See Technical Data Sheet.

1.3. Details of the supplier of the safety data sheet

Company Name	SAF-T-LOK International Corporation 300 EISENHOWER LANE NORTH LOMBARD, IL 60148
---------------------	---

Emergency	
CHEMTREC (USA)	(800) 424-9300
24 hour Emergency Telephone No.	(703) 527-3887
Customer Service: SAF-T-LOK International Corporation	(630) 495-2001

2. Hazard identification of the product

2.1. Classification of the substance or mixture

Skin Sensitization	Category 1	May cause an allergic skin reaction
Carcinogenicity	Category 2	Suspected of causing cancer
Specific Target Organ Toxicity (repeated exposure)	Category 1	Causes damage to organs (lung, respiratory system) through prolonged or repeated exposure

2.2. Label elements

Using the Toxicity Data listed in section 11 and 12 the product is labeled as follows.

Warning

Safety Data Sheet
NICKEL PREMIUM ANTI-SEIZE

SDS Revision Date:

07/31/2018



H313 May be harmful in contact with skin.

[Prevention]:

P273 Avoid release to the environment
 Obtain special instructions before use
 Do not breathe dust/fume/gas/mist/vapor/spray
 Wear protective gloves

[Response]:

P390 Collect spillage
 Allergic skin reaction
 Suspected of causing cancer
 Causes damage to organs (lung, respiratory system) through prolonged or repeated exposure
 P312 Call a POISON CENTER or doctor / physician if you feel unwell.

[Storage]:

No GHS storage statements

[Disposal]:

No GHS disposal statements

3. Composition/information on ingredients

This product contains the following substances that present a hazard within the meaning of the relevant State and Federal Hazardous Substances regulations.

Ingredient/Chemical Designations	Weight %	GHS Classification	Notes
Petroleum distillates, hydrotreated heavy naphthenic CAS Number: 0064742-52-5	50-70	Acute Tox. 4; H312	[1]
Graphite CAS Number: 0007782-42-5	8-30		[1]
Nickel CAS Number: 007440-02-0	8-30	Skin sensitization, 1; H317 Carcinogenicity, 2; H351	[1][2]
Aluminum CAS Number: 007429-90-5	1-10		[1][2]

[1] Substance classified with a health or environmental hazard.

[2] Substance with a workplace exposure limit.

[3] PBT-substance or vPvB-substance.

*The full texts of the phrases are shown in Section 16.

4. First aid measures

4.1. Description of first aid measures

General	In all cases of doubt, or when symptoms persist, seek medical attention. Never give anything by mouth to an unconscious person.
Inhalation	Remove to fresh air, keep patient warm and at rest. If breathing is irregular or stopped, give artificial respiration. If unconscious place in the recovery position and obtain immediate medical attention. Give nothing by mouth.
Eyes	Irrigate copiously with clean water for at least 15 minutes, holding the eyelids apart and seek medical attention.
Skin	Remove contaminated clothing. Wash skin thoroughly with soap and water or use a recognized skin cleanser.
Ingestion	If swallowed obtain immediate medical attention. Keep at rest. Do NOT induce vomiting.

4.2. Most important symptoms and effects, both acute and delayed

Overview	<p>Skin Contact: Usually no effect, however, as with any chemical, prolonged, excessive, or repeated exposure may cause mild to moderate skin irritation, exhibited by redness, drying and cracking of unprotected skin.</p> <p>Eye Contact: May irritate with slight pain and redness.</p> <p>Respiratory/ Inhalation: Usually none, however, as with any chemical product, some irritation may occur.</p> <p>Ingestion: Rinse mouth thoroughly if ingested. Do not induce vomiting. Amounts transferred to mouth by fingers, etc, during normal operation should not cause injury. Get medical attention if any discomfort continues.</p> <p>Medical conditions generally aggravated by exposure: None known, however any chemical product may enhance allergies already present in certain individuals.</p> <p>This product does not require exceptional labeling due to the evaluation procedure of the "General Classification guideline for preparations of the EU". See section 2 for further details.</p>
Skin	May be harmful in contact with skin. (Not adopted by US OSHA)

5. Fire-fighting measures

5.1. Extinguishing media

Recommended extinguishing media; alcohol resistant foam, CO₂, powder, water spray.
Do not use; water jet.

5.2. Special hazards arising from the substance or mixture

Hazardous decomposition: Oxides of carbon and sulfur

5.3. Advice for fire-fighters

Air mask and procedures for fighting chemical fires. Do not inhale gases.

Treat as an oil fire. Use a full-faced self-contained breathing apparatus along with full protective gear. Keep nearby containers and equipment cool with a water stream.

ERG Guide No. ----

6. Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Put on appropriate personal protective equipment (see section 8).

6.2. Environmental precautions

Do not allow spills to enter drains or waterways.

Use good personal hygiene practices. Wash hands before eating, drinking, smoking or using toilet. Promptly remove soiled clothing and wash thoroughly before reuse.

6.3. Methods and material for containment and cleaning up

Prevent material from entering floor drains, sewers, or any bodies of water.

Scoop up into waste container or soak up with absorbent material. Store in a closed container until disposal.

7. Handling and storage

7.1. Precautions for safe handling

See section 2 for further details. - [Prevention]:

7.2. Conditions for safe storage, including any incompatibilities

No special precautions necessary if used properly. Avoid breathing vapors. Wash hands thoroughly at mealtime and end of shift.

Isolated storage facility/ warehouse not required. Store in a cool, dry location (60-90°F) in a well-ventilated area in original container. Keep container tightly closed when not in use.

Incompatible materials: Strong Oxidizing Agents, Strong Acids and Alkalis.

See section 2 for further details. - [Storage]:

7.3. Specific end use(s)

None

8. Exposure controls and personal protection

8.1. Control parameters

CAS No.	Ingredient	Exposure	
		Source	Value
0007782-42-5	Graphite	OSHA	TWA: 15 mg/m ³ TWA: 15 mppcf
		ACGIH	TWA: 2 mg/m ³
		NIOSH	TWA: 2.5 mg/m ³ (resp)
		Supplier	No Established Limit
0007440-02-0	Nickel	OSHA	No Established Limit
		ACGIH	No Established Limit
		NIOSH	No Established Limit
		Supplier	No Established Limit
0064742-52-5	Petroleum distillates, hydrotreated heavy naphthenic	OSHA	No Established Limit
		ACGIH	No Established Limit
		NIOSH	No Established Limit
		Supplier	No Established Limit
0007429-90-5	Aluminum	OSHA	TWA: 15 mg/m ³ (Total) TWA 5 mg/m ³ (resp)
		ACGIH	TWA: 1.0 mg/m ³ revised 2008
		NIOSH	TWA 10 mg/m ³ (Total) TWA 5 mg/m ³ (resp)
		Supplier	No Established Limit

Contains mineral oil. The exposure limits for oil mist are 5 mg/m³ OSHA PEL and 10 mg/m³ ACGIH.

Carcinogen Data

CAS No.	Ingredient	Source	Value
0007429-90-5	Aluminum	OSHA	Select Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;
0007440-02-01	Nickel	OSHA	Select Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;
0007782-42-5	Graphite	OSHA	Select Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;
0064742-52-5	Petroleum distillates, hydrotreated heavy naphthenic	OSHA	Select Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;

8.2. Exposure controls

Respiratory

No respiratory protection required, but normal good ventilation is recommended. Forced ventilation may be required if concentrations exceed normal use exposure.

Eyes	Not required if application method is proper. Avoid contact with eyes.
Skin	Wear overalls to keep skin contact to a minimum. Use impermeable gloves (neoprene, butyl rubber, natural rubber), as necessary to avoid skin contact, as well as proper clothing or plastic apron. Wash hands before eating, drinking, or using restroom.
Engineering Controls	Provide adequate ventilation. Where reasonably practicable this should be achieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations of particulates and any vapor below occupational exposure limits suitable respiratory protection must be worn.
Other Work Practices	Eye wash stations should be located within 100 feet or 10 second walk of the work area. Use good personal hygiene practices. Wash hands before eating, drinking, smoking or using toilet. Promptly remove soiled clothing and wash thoroughly before reuse.

See section 2 for further details. - [Prevention]:

9. Physical and chemical properties

Appearance	Silver Grey Paste
Odor	Mild/Inoffensive
Odor threshold	Not Measured
pH	Not determined
Melting point / freezing point	Not determined
Initial boiling point and boiling range	600 F (316 C)
Flash Point	350 F (C.O.C.)
Evaporation rate (Ether = 1)	Not determined
Flammability (solid, gas)	Not Applicable
Upper/lower flammability or explosive limits	Lower Explosive Limit: N/A Upper Explosive Limit: N/A
Vapor pressure (Pa)	<0.1 @ 70 F (mm Hg.)
Vapor Density	N/D
Specific Gravity	1.28
Solubility in Water	Insoluble
Partition coefficient n-octanol/water (Log Kow)	Not Measured
Auto-ignition temperature	Not Measured
Decomposition temperature	Not Measured
Viscosity (cSt)	Not Measured
VOC %	<0.1% (Organic solvents)%(cut)
% Solid	35-50

9.2. Other information

DMSO extract by IP346: Less than 3.0 wt % (mineral oil component only)

10. Stability and reactivity

10.1. Reactivity

Hazardous Polymerization will not occur.

10.2. Chemical stability

Safety Data Sheet
NICKEL PREMIUM ANTI-SEIZE

SDS Revision Date:

07/31/2018

Stable under normal circumstances.

10.3. Possibility of hazardous reactions

No data available.

10.4. Conditions to avoid

Incompatible with strong oxidizing agents

10.5. Incompatible materials

Strong Oxidizing Agents, Strong Acids and Alkalis.

10.6. Hazardous decomposition products

Oxides of carbon and sulfur

11. Toxicological information

Acute toxicity

Ingredient	Oral LD50, mg/kg	Skin LD50, mg/kg	Inhalation Vapor LD50, mg/L/4hr	Inhalation Dust/Mist LD50, mg/L/4hr	Inhalation Gas LD50, ppm
Petroleum distillates, hydrotreated heavy naphthenic - (64742-52-5)	5,000.00, Rat - Category: 5	2,000.00, Rabbit - Category: 4	No data available	No data available	No data available
Graphite-(0007782-42-5)	No data available	No data available	No data available	No data available	No data available
Nickel- (0007440-02-0)	>9000 mg/kg (Rat)	No data available	No data available	No data available	No data available
Aluminum- (0007429-90-5)	No data available	No data available	No data available	No data available	No data available

Note: When no route specific LD50 data is available for an acute toxin, the converted acute toxicity point estimate was used in the calculation of the product's ATE (Acute Toxicity Estimate).

Classification	Category	Hazard Description
Acute toxicity (oral)	---	Not Applicable
Acute toxicity (dermal)	5	May be harmful in contact with skin. (Not adopted by US OSHA)
Acute toxicity (inhalation)	---	Not Applicable
Skin corrosion/irritation	---	Not Applicable
Serious eye damage/irritation	---	Not Applicable
Respiratory sensitization	---	Not Applicable
Skin sensitization	---	Not Applicable
Germ cell mutagenicity	---	Not Applicable
Carcinogenicity	---	Suspected by inhalation
Reproductive toxicity	---	Not Applicable
STOT-single exposure	---	Not Applicable

STOT-repeated exposure	---	Not Applicable
Aspiration hazard	---	Not Applicable

12. Ecological information

12.1. Toxicity

No additional information provided for this product. See Section 3 for chemical specific data.

Aquatic Ecotoxicity

Ingredient	96 hr LC50 fish, mg/l	48 hr EC50 crustacea, mg/l	ErC50 algae, mg/l
Petroleum distillates, hydrotreated heavy naphthenic - (64742-52-5)	5,000.00, Oncorhynchus mykiss	1,000.00, Daphnia magna	1,000.00 (96 hr), Scenedesmus subspicatus
Graphite – (0007782-42-5)	Not Available	Not Available	Not Available
Nickel - (0007440-02-0)	1.3 mg/L LC50 Cyprinus carpio 96h semi-static 10.4 mg/L LC50 Cyprinus carpio 96h static 1000 mg/L LC50 Brachydanio rerio 96h	1 mg/L Daphnia magna 48h Static 100 mg/L EC50 Daphnia magna 48h	0.18 mg/L EC50 Pseudokirchnerilla subcapitata 72h 0.174 – 0.311 mg/L EC50 Pseudokirchnerilla subcapitata 96h static
Aluminum - (0007429-90-5)	Not Available	Not Available	Not Available

12.2. Persistence and degradability

There is no data available on the preparation itself.

12.3. Bioaccumulative potential

Not Measured

12.4. Mobility in soil

No data available.

12.5. Results of PBT and vPvB assessment

This product contains no PBT/vPvB chemicals.

12.6. Other adverse effects

No data available.

13. Disposal considerations

13.1. Waste treatment methods

Observe all federal, state and local regulations when disposing of this substance.

14. Transport information

Safety Data Sheet
NICKEL PREMIUM ANTI-SEIZE

SDS Revision Date:

07/31/2018

	DOT (Domestic Surface Transportation)	IMO / IMDG (Ocean Transportation)	ICAO/IATA
14.1. UN number	Not Applicable	Not Regulated	Not Regulated
14.2. UN proper shipping name	Not Regulated	Environmentally hazardous substance, liquid, N.O.S	
14.3. Transport hazard class(es)	DOT Hazard Class: Not Applicable DOT Label: ---	IMDG: 9 Sub Class: Not Applicable	Air Class: Not Applicable
14.4. Packing group	Not Applicable	Not Applicable	Not Applicable
14.5. Environmental hazards			
IMDG	Not Applicable		
14.6. Special precautions for user			
	No further information		

15. Regulatory information

Regulatory Overview The regulatory data in Section 15 is not intended to be all-inclusive, only selected regulations are represented.

Toxic Substance Control Act (TSCA) All components of this material are either listed or exempt from listing on the TSCA Inventory.

WHMIS Classification Not Regulated

US EPA Tier II Hazards

Fire: No
Sudden Release of Pressure: No
Reactive: No
Immediate (Acute): Yes
Delayed (Chronic): No

EPCRA 311/312 Chemicals and RQs:
 (No Product Ingredients Listed)

EPCRA 302 Extremely Hazardous :
 (No Product Ingredients Listed)

EPCRA 313 Toxic Chemicals:
 (No Product Ingredients Listed)

Proposition 65 - Carcinogens (>0.0%):
 Nickel

Proposition 65 - Developmental Toxins (>0.0%):
 (No Product Ingredients Listed)

Proposition 65 - Female Repro Toxins (>0.0%):
 (No Product Ingredients Listed)

Proposition 65 - Male Repro Toxins (>0.0%):
 (No Product Ingredients Listed)

N.J. RTK Substances (>1%):

- Aluminum
- Nickel
- Graphite

Penn RTK Substances (>1%):

- Aluminum

Nickel
Graphite

16. Other information

The information and recommendations contained herein are based upon data believed to be correct. However, no guarantee or warranty of any kind, expressed or implied, is made with respect to the information contained herein. We accept no responsibility and disclaim all liability for any harmful effects, which may be caused by exposure to our products. Customers/users of this product must comply with all applicable health and safety laws, regulations, and orders.

The full text of the phrases appearing in section 3 is:

H312 Harmful in contact with skin.

This is the first version in the GHS SDS format. Listings of changes from previous versions in other formats are not applicable.

The information on this material safety data sheet represents our current data and best opinion as to the proper use in handling of this product under normal conditions. Any use of the product which is not in conformance with this data sheet or which involves using the product in combination with any other product or any other process is the responsibility of the user. SAF-T-LOK International Corporation specifically disclaims all warranties, express or implied, including warranties of merchantability and fitness for a particular purpose, arising from sale or use of SAF-T-LOK International Corporation products.

End of Document