

EP2 GREASE

Spanjaard EP2 Grease is a high quality, all purpose, and lithium-based grease.

APPLICATIONS

Suitable for lubrication of plain, needle, ball and roller bearing of all types. **Spanjaard EP2 Grease** is fortified with rust and oxidation inhibitors.

Spanjaard EP2 Grease is suitable for lubrication of automotive, industrial equipment and mining equipment.

APPLICATION INSTRUCTIONS

Apply by hand or grease gun. Compatible with other competitive lithium greases. It is always a good practice to flush out old grease when switching lubricants. This is achieved by frequent re-greasing over a short time span.

It is essential that dust and dirt do not get into the bearings and care must be taken to prevent this during grease storage and packing of bearings.

HANDLING AND STORAGE

Store under cover with lid closed away from vibrating floor. Remove excess from skin and wash with Spanjaard Hand Cleaner followed by soap and water.

TYPICAL PROPERTIES

Colour	Beige
Consistency - NLGI grade	2
Worked Penetration, 25°C, 1/10mm	280
Thickener	Lithium Soap
Appearance Texture	Smooth
Drop Point, °C	>180
Dynamic Rust Test	<1
Copper Corrosion - 24hr/100°C	Pass
Oil Separation 18h @ 40°C, %	<2
Water Wash Out @ 38°C, %	<2
@ 79°C, %	<4
Rust Prevention	Pass
Timken OK Load, kg	>27
Operating Temperature	
Continuous service, °C	-20 to 120

BASE OIL PROPERTIES

Oil Viscosity cSt, 40°C	200
Flash Point, °C	>225



PACKAGING

400g cartridge; 500g; 5kg; 15kg; 50kg; 180kg.

CP/mg/ EP 2 Grease – Sep 2017