

**SIDDHARTH GREASE & LUBES PRIVATE LIMITED****Plot # 13, Sector-3, IMT Manesar-122050, India**

Tel. No.:+91-124-4615100,Fax No.: +91-124-4615199

www.siddharthpetro.com**(An ISO 9001:2015,ISO14001:2015 &ISO 45001:2018 Certified Company)****PRODUCT- SGL CSG2 V460 Grease****PRODUCT DATA SHEET**

Issue Date: 20.12.2024

Issued to:
United Oil Vietnam Company Ltd.

S No.	Characteristics	Test Method	Control Limits
1.	Appearance & Color		Smooth, homogeneous, & Brown
2.	NLGI Grade	ASTM D217	2
3.	Thickener	Formulation	Calcium Sulfonate Complex
4.	Consistency		
5.	Penetration worked 60X	ASTM D217	265-295
6.	Base Oil Properties		
7.	Base Oil, KV @ 40° C, cSt	ASTM D445	VG460 (±10%)
8.	Base Oil Type	-	Mineral
9.	Dropping Point, °C	ASTM D2265	260 Min.
10.	Copper Strip Corrosion @ 100°C, 24 hrs.	ASTM D4048	1b Max
11.	Performance Test		
12.	Oil Separation, % wt	ASTM D1742	10 Max
13.	Resistance to water washout, % wt. loss	ASTM D 1264	10 Max
14.	Additive Function		
15.	Dynamic Rust Test in D/W (SKF EMCOR)	ASTM D 6138	0,0
16.	4 Ball weld load, kgf	IP 239	500 min.
17.	Operating Temperature Range	Internal	-10°C to +180°C

